

Product Name / Type:	AMERICANA CHALET		Tongue & Groove Engineered Plank	
Engineered Construction Details / Certifications:	Balanced 5-crossed ply real hardwood layers; Product specific top/bottom plys, with 3-ply Poplar (<i>liriodendron tulipifera</i>) core. Nominal 2mm (1/12") rotary peeled top layer on all items. Cross Linked PVA based ply adhesive. Certifications: Floorscore Certified; Manufactured Using Carb Phase II and TSCA Title VI Compliant Materials. Harris Wood follows responsible sourcing guidelines from legal, well managed, sustainable forests.			
Plank Surface / Finish	Smooth	Edge Treatment;	Microbeveled	
Finish Type:	FinishLoc	Plank Profile:	Tongue & Groove	
Surface Gloss:	Ultra Low			
Finish Warranty:	Residential:	Lifetime	* Light Commercial:	3 years
* Structural Warranty:	Residential:	Lifetime	* Light Commercial:	10 years

*** Light Commercial Warranty applies to Oak, Hickory, and Maple Species Products.**

Refinishing Options (when professionally performed):	On 2mm and above top layer items, can sand & refinish 1 time to repair excessive wear/damaged floors. (Alt.) Screen & Recoat to improve finish luster / non-penetrating scratches, etc.. Note: (1) Stain may remain on beveled edges. (2) Textured surfaces will be affected by sanding and refinishing.
--	--

ENGINEERED TONGUE & GROOVE INSTALLATION OPTIONS:

T&G

(A) Floating, glue T&G method, over cushioning type underlayment (purchased separately); (B) Troweled full-spread glue down to subfloor; (C) Staple/Nail direct to wood subfloor

INSTALLATION LOCATIONS: Indoor climate controlled areas (60-80F, 35-55% RH); On / Above / Below Grade; in most rooms (excluding full baths); Over in-floor radiant heat ? (Harris Wood approves Engineered Oak, American Cherry, Walnut Species ONLY); Not approved for use on stairs / treads.

APPROVED SUBFLOORS: Structurally sound, flat, firm, dry, and clean hard surfaces such as plywood, OSB, and concrete (see installation instructions for additional details). When FLOATING only, also particleboard and lightweight concrete.

P65 WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood-dust

PLANK SPECS: 5" W x 3/8" T x RL (12" to 46-1/4")				SQ FT / LBS PER CTN (28 PER PLT.)	COORDINATING REAL WOOD MOLDINGS				
WOOD SPECIES (Top Layer)	COLOR	ITEM #		Flush Mount Reducer	Flush Mount Stairnose	T Mold	Qtr. Rd.	Threshold	
				All moldings 78" Length. Packed 5 pcs. per ctn.					
HICKORY (<i>Carya spp.</i>)									
Vintage Hickory (2.0mm)	Roaring Fork	HE2331	34/ 48.0	LM6810	LM6811	LM6812	LM6813	LM6814	
Vintage Hickory (2.0mm)	Silverdale	HE2330	34/ 48.0	LM6815	LM6816	LM6817	LM6818	LM6819	
MAPLE (<i>Acer saccharum</i>)									
Vintage Maple (2.0mm)	Monarch	HE2339	34/ 48.0	LM6869	LM6870	LM6871	LM6872	LM6873	
WALNUT (<i>Juglas nigra</i>)									
Walnut (2.0mm)	Alpine	HE2333	34/ 48.0	LM6825	LM6826	LM6827	LM6828	LM6829	
Walnut (2.0mm)	Willow	HE2334	34/ 48.0	LM6874	LM6875	LM6876	LM6877	LM6878	

Vintage and Rustic products may contain naturally occurring light and dark wood color and grain variations.

* Sunlight exposure and artificial lighting will alter the appearance of all wood floors over time. Domestic Exotics (American Cherry and Walnut) are typically more prone to change than other species.

FEATURES / BENEFITS: Smooth or Surface real hardwood flooring with a ultra low gloss finish and trending colors • Traditional Tongue and Groove installation allows multiple methods including floating (glue T&G method over cushioning underlayment), troweled full-spread glue down directly to the subfloor, staple /nail down. • Durable 5-ply real hardwood construction offers maximum stability • Urethane Aluminum Oxide Finish provides superior wear, scuff, gloss reduction, and staining resistance • Hypo-allergenic, does not harbor allergens.

Made In USA Established
1898



MANUFACTURED USING CARB
PHASE II AND TSCA TITLE VI
COMPLIANT MATERIALS