

Product Name / Type:	<b>AMERICANA COTTAGE</b>		<b>Tongue &amp; Groove Engineered Plank</b>	
Engineered Construction Details / Certifications:	Balanced 5-crossed ply real hardwood layers; Product specific top/bottom plys, with 3-ply Poplar ( <i>liriodendron tulipifera</i> ) core. Nominal 2mm (1/12") rotary peeled top layer on all items. Cross Linked PVA based ply adhesive. Certifications: Floorscore Certified; Manufactured Using Carb Phase II and TSCA Title VI Compliant Materials. Harris Wood follows responsible sourcing guidelines from legal, well managed, sustainable forests.			
Plank Surface:	Smooth	Edge Treatment:	Microbeveled	
Finish Type:	Urethane with Aluminum Oxide	Plank Profile:	Tongue & Groove	
Surface Gloss:	Satin			
Finish Warranty:	Residential:	25 Years	Light Commercial:	N/A
Structural Warranty:	Residential:	Lifetime	Light Commercial:	N/A

**Refinishing Options (when professionally performed):** On 2mm and above top layer items, can sand & refinish 1 time to repair excessive wear/damaged floors. (Alt.) Screen & Recoat to improve finish luster / non-penetrating scratches, etc.. Note: (1) Stain may remain on beveled edges. (2) Textured surfaces will be affected by sanding and refinishing.

**ENGINEERED TONGUE & GROOVE INSTALLATION OPTIONS:**

**T&G** (A) Floating, glue T&G method, over cushioning type underlayment (purchased separately); (B) Troweled full-spread glue down to subfloor; (C) Staple/Nail direct to wood subfloor

**INSTALLATION LOCATIONS:** Indoor climate controlled areas (60-80F, 35-55% RH); On / Above / Below Grade; in most rooms (excluding full baths); Over in-floor radiant heat ? (Harris Wood approves Engineered Oak, American Cherry, Walnut Species ONLY); Not approved for use on stairs / treads.

**APPROVED SUBFLOORS:** Structurally sound, flat, firm, dry, and clean hard surfaces such as plywood, OSB, and concrete (see installation instructions for additional details). When FLOATING only, also particleboard and lightweight concrete.

**P65 WARNING:** Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to [www.P65Warnings.ca.gov/wood-dust](http://www.P65Warnings.ca.gov/wood-dust)

PLANK SPECS: 5" W x 3/8" T x RL (12" to 46-1/4")			SQ FT / LBS PER CTN (28 PER PLT.)	COORDINATING REAL WOOD MOLDINGS						
WOOD SPECIES (Top Layer)	COLOR	ITEM #		Lipover Reducer	Flush Mount Reducer	Lipover Stairnose	Flush Mount Stairnose	T Mold	Qtr. Rd.	Threshold
				All moldings 78" Length. Packed 5 pcs. per ctn.						
<b>RED OAK (<i>Quercus rubra</i>)</b>										
Red Oak (2.0mm)	Natural	HE1000	34/48.0	LM6270	LM3870	LM6335	LM3880	LM3259.5	LM3274.3	LM4503
Red Oak (2.0mm)	Colonial	HE1001	34/48.0	LM6274	LM6286	LM6339	LM6295	LM5910	LM5907	LM6312
Red Oak (2.0mm)	Dark Gunstock	HE1002	34/ 48.0	LM6272	LM4389	LM6337	LM4396	LM4404	LM4475	LM4482
<b>HICKORY (<i>Carya spp.</i>)</b>										
Vintage Hickory (2.0mm)	Natural	HE1200	34/ 48.0	LM6278	LM4775	LM6343	LM4782	LM4558	LM4563	LM4597
<b>MAPLE (<i>Acer saccharum</i>)</b>										
Vintage Maple (2.0mm)	Natural	HE1600	34/ 48.0	LM6275	LM4778	LM6340	LM4785	LM3249	LM3263	LM5938

**Vintage and Rustic products may contain naturally occurring light and dark wood color and grain variations.**

**FEATURES / BENEFITS:** Smooth Surface real hardwood flooring with a satin finish and popular colors • Perfect for the builder market • Traditional Tongue and Groove installation allows multiple methods including floating (glue T&G method over cushioning underlayment), troweled full-spread glue down directly to the subfloor, staple /nail down. • Durable 5-ply real hardwood construction offers maximum stability • Urethane Aluminum Oxide Finish provides superior wear, scuff, gloss reduction, and staining resistance • Hypo-allergenic, does not harbor allergens.

**Made In USA Established 1898**



**MANUFACTURED USING CARB PHASE II AND TSCA TITLE VI COMPLIANT MATERIALS**