

Product Name / Type:	AMERICANA MOUNTAINS		Tongue & Groove Engineered Plank	
Engineered Construction Details / Certifications:	Balanced 5-crossed ply real hardwood layers; Product specific top/bottom plys, with 3-ply Poplar (<i>liriodendron tulipifera</i>) core. Nominal 2mm (1/12") sliced top layer on all items. Cross Linked PVA based ply adhesive. Certifications: Floorscore Certified; Manufactured Using Carb Phase II and TSCA Title VI Compliant Materials. Harris Wood follows responsible sourcing guidelines from legal, well managed, sustainable forests.			
Plank Surface / Finish	Smooth or Wirebrushed	Edge Treatment;	Microbeveled	
Finish Type:	Urethane with Aluminum Oxide	Plank Profile:	Tongue & Groove	
Surface Gloss:	Ultra Low (OAK, HICKORY): Low (MAPLE)			
Finish Warranty:	Residential:	Lifetime	* Light Commercial:	3 years
* Structural Warranty:	Residential:	Lifetime	* Light Commercial:	10 years
* Light Commercial Warranty applies to Oak, Hickory, and Maple Species Products.				
Refinishing Options (when professionally performed):	On 2mm and above top layer items, can sand & refinish 1 time to repair excessive wear/damaged floors. (Alt.) Screen & Recoat to improve finish luster / non-penetrating scratches, etc.. Note: (1) Stain may remain on beveled edges. (2) Textured surfaces will be affected by sanding and refinishing.			

ENGINEERED TONGUE & GROOVE INSTALLATION OPTIONS:

T&G (A) Floating, glue T&G method, over cushioning type underlayment (purchased separately); (B) Troweled full-spread glue down to subfloor; (C) Staple/Nail direct to wood subfloor

INSTALLATION LOCATIONS: Indoor climate controlled areas (60-80F, 35-55% RH); On / Above / Below Grade; in most rooms (excluding full baths); Over in-floor radiant heat ? (Harris Wood approves Engineered Oak, American Cherry, Walnut Species ONLY); Not approved for use on stairs / treads.

APPROVED SUBFLOORS: Structurally sound, flat, firm, dry, and clean hard surfaces such as plywood, OSB, and concrete (see installation instructions for additional details). When FLOATING only, also particleboard and lightweight concrete.

P65 WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood-dust

PLANK SPECS: 7-1/2" W x 1/2" T x Fixed RL (24" to 95-1/2")			SQ FT / LBS PER CTN (28 PER PLT.)	COORDINATING REAL WOOD MOLDINGS				
WOOD SPECIES (Top Layer)	COLOR	ITEM #		Flush Mount Reducer	Flush Mount Stairnose	T Mold	Qtr. Rd.	Threshold
WIREBRUSHED TEXTURED SURFACE				All moldings 78" Length. Packed 5 pcs. per ctn.				
RED OAK (<i>Quercus rubra</i>)								
Red Oak (2.0mm)	LeConte	HE96000	29.75/ 45.0	LM7475	LM7476	LM7477	LM7478	LM7479
Red Oak (2.0mm)	Denali	HE96002	29.75/ 45.0	LM7485	LM7486	LM7487	LM7488	LM7489
Hickory (2.0mm)	Bryce	HE96007	29.75/ 45.0	LM7535	LM7536	LM7537	LM7538	LM7539
SMOOTH SURFACE								
WHITE OAK (<i>Quercus alba</i>)								
White Oak (2.0mm)	Wonderland	HE96012	29.75/ 45.0	LM7585	LM7586	LM7587	LM7588	LM7589
HICKORY (<i>Carya spp.</i>)								
Hickory (2.0mm)	Wrangell	HE96015	29.75/ 45.0	LM7610	LM7611	LM7612	LM7613	LM7614
Hickory (2.0mm)	Windom	HE96018	29.75/ 45.0	LM7580	LM7581	LM7582	LM7583	LM7584
Hickory (2.0mm)	Palisade	HE96022	29.75/ 45.0	LM7723	LM7724	LM7725	LM7727	LM7726
MAPLE (<i>Acer saccharum</i>)								
Maple (2.0mm)	Half Dome	HE96019	29.75/ 45.0	LM7700	LM7701	LM7702	LM7704	LM7703
Maple (2.0mm)	Olympic	HE96023	29.75/ 45.0	LM7728	LM7729	LM7730	LM7732	LM7731
Maple (2.0mm)	Bighorn	HE96021	29.75/ 45.0	LM7718	LM7719	LM7720	LM7722	LM7721

Vintage and Rustic products may contain naturally occurring light and dark wood color and grain variations.

FEATURES / BENEFITS: Wide & Long Plank Smooth or Wirebrushed Surface real hardwood flooring with a broad selection of colors • Sliced surface veneers create the look of traditional solid hardwood in these engineered plank floors • Traditional Tongue and Groove installation allows multiple methods including floating (glue T&G method over cushioning underlayment), troweled full-spread glue down directly to the subfloor, staple /nail down. • Durable 5-ply real hardwood construction offers maximum stability • Urethane Aluminum Oxide Finish provides superior wear, scuff, gloss reduction, and staining resistance • Hypo-allergenic, does not harbor allergens.

Made In USA
Established 1898



**MANUFACTURED USING CARB
PHASE II AND TSCA TITLE VI
COMPLIANT MATERIALS**