

Product Name / Type:	AMERICANA WATERCREST		Glueless Locking Engineered Plank	
Engineered Construction Details / Certifications:	Balanced 5-crossed ply real hardwood layers; Product specific top/bottom plys, with 3-ply Poplar (<i>liriodendron tulipifera</i>) core. Nominal 1.2mm (1/21") sliced top layer on OAK and HICKORY items. Nominal 2mm (1/12") rotary peeled top layer on MAPLE items. Cross Linked PVA based ply adhesive. Certifications: Floorscore Certified; Manufactured Using Carb Phase II and TSCA Title VI Compliant Materials. Harris Wood follows responsible sourcing guidelines from legal, well managed, sustainable forests.			
Plank Surface / Finish	Smooth / Low or Very Low Gloss	Edge Treatment;		Microbeveled
Finish Type:	Urethane with Aluminum Oxide	Plank Profile:		Glueless Locking
Surface Gloss:	Ultra Low (OAK, HICKORY): Low (MAPLE)			
Finish Warranty:	Residential:	Lifetime	* Light Commercial:	3 years
* Structural Warranty:	Residential:	Lifetime	* Light Commercial:	10 years

* Light Commercial Warranty applies to Oak, Hickory, and Maple Species Products.

Refinishing Options (when professionally performed):	On 2mm and above top layer items, can sand & refinish 1 time to repair excessive wear/damaged floors. (Alt.) Screen & Recoat to improve finish luster / non-penetrating scratches, etc.. Note: (1) Stain may remain on beveled edges. (2) Textured surfaces will be affected by sanding and refinishing.
--	--

**CLICK
LOCK**

GLUELESS LOCKING INSTALLATION OPTIONS:

(A) Floating over cushioning type underlayment (purchased separately), and (B) Troweled full-spread glue down directly to subfloor.

INSTALLATION LOCATIONS: Indoor climate controlled areas (60-80F, 35-55% RH); On / Above / Below Grade; in most rooms (excluding full baths); Over in-floor radiant heat ? (Harris Wood approves Engineered Oak, American Cherry, Walnut Species ONLY); Not approved for use on stairs / treads.

APPROVED SUBFLOORS: Structurally sound, flat, firm, dry, and clean hard surfaces such as plywood, OSB, and concrete (see installation instructions for additional details). When FLOATING only, also particleboard and lightweight concrete.

P65 WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood-dust

PLANK SPECS: 6-1/4" W x 3/8" T x RL (12" to 46-1/4")			SQ FT / LBS	COORDINATING REAL WOOD MOLDINGS						
WOOD SPECIES (Top Layer)	COLOR	ITEM #	PER CTN (28 PER PLT.)	Lipover Reducer	Flush Mount Reducer	Lipover Stairnose	Flush Mount Stairnose	T Mold	Qtr. Rd.	Threshold
RED OAK (<i>Quercus rubra</i>)				All moldings 78" Length. Packed 5 pcs. per ctn.						
Red Oak (1.2mm)	Allegheny	HE62501	32.2/ 48.0	LM6270	LM3870	LM6335	LM3880	LM3259.5	LM3274.3	LM4503
Red Oak (1.2mm)	Kenai	HE62502	32.2/ 48.0	LM7426	LM7712	LM7713	LM7427	LM7429	LM7428	LM7710
Red Oak (1.2mm)	St. Lawrence	HE62503	32.2/ 48.0	LM7430	LM7714	LM7715	LM7431	LM7433	LM7432	LM7711
Red Oak (1.2mm)	Potomac	HE62510	32.2/ 48.0	LM6274	LM6286	LM6339	LM6295	LM5910	LM5907	LM6312
HICKORY (<i>Carya spp.</i>)										
Hickory (1.2mm)	Allagash	HE62505	32.2/ 48.0	LM6278	LM4775	LM6343	LM4782	LM4558	LM4563	LM4597
Hickory (1.2mm)	Hudson	HE62506	32.2/ 48.0	LM7542	LM7547	LM7552	LM7557	LM7562	LM7572	LM7567
Hickory (1.2mm)	Merced	HE62509	32.2/ 48.0	LM7716	LM6864	LM7717	LM6865	LM6866	LM6867	LM6868
MAPLE (<i>Acer saccharum</i>)										
Maple (2.0mm)	Cimarron	HE62507	32.2/ 48.0	LM7543	LM7548	LM7553	LM7558	LM7563	LM7573	LM7568
Maple (2.0mm)	Tallulah	HE62508	32.2/ 48.0	LM7544	LM7549	LM7554	LM7559	LM7564	LM7574	LM7569
Maple (2.0mm)	Klamath	HE62511	32.2/ 48.0	LM6275	LM4778	LM6340	LM4785	LM3249	LM3263	LM5938

Vintage and Rustic products may contain naturally occurring light and dark wood color and grain variations.

FEATURES / BENEFITS: Smooth surface real hardwood planks with a broad selection of colors featuring a user friendly installation system • Oak and Hickory items feature a sliced surface veneer that creates the look of solid wood in these engineered plank floors • Glueless Locking system allows quick floating installation (can also be troweled full-spread glued directly to the subfloor) • Durable 5-ply real hardwood construction offers maximum stability • Urethane Aluminum Oxide Finish provides superior wear, scuff, gloss reduction, and staining resistance • Hypo-allergenic, does not harbor allergens.

**Made In USA Established
1898**



**MANUFACTURED USING CARB
PHASE II AND TSCA TITLE VI
COMPLIANT MATERIALS**