

Product Name / Type:	AMERICANA MOUNTAINS		Tongue & Groove Engineered Plank	
Engineered Construction Details / Certifications:	Balanced 5-crossed ply real hardwood layers; Product specific top/bottom plys, with 3-ply Poplar (<i>liriodendron tulipifera</i>) core. Nominal 2mm (1/12") sliced top layer on Oak and Hickory items, 2.3mm on Maple items. Cross Linked PVA based ply adhesive. Certifications: Floorscore Certified; Manufactured Using Carb Phase II and TSCA Title VI Compliant Materials. Harris Wood follows responsible sourcing guidelines from legal, well managed, sustainable forests.			
Plank Surface / Finish	Smooth or Wirebrushed	Edge Treatment;	Microbeveled	
Finish Type:	Urethane with Aluminum Oxide	Plank Profile:	Tongue & Groove	
Surface Gloss:	Ultra Low (OAK, HICKORY): Low (MAPLE)			
Finish Warranty:	Residential:	Lifetime	* Light Commercial:	3 years
* Structural Warranty:	Residential:	Lifetime	* Light Commercial:	10 years
* Light Commercial Warranty applies to Oak, Hickory, and Maple Species Products.				
Refinishing Options (when professionally performed):	On 2mm and above top layer items, can sand & refinish 1 time to repair excessive wear/damaged floors. (Alt.) Screen & Recoat to improve finish luster / non-penetrating scratches, etc.. Note: (1) Stain may remain on beveled edges. (2) Textured surfaces will be affected by sanding and refinishing.			

T&G **ENGINEERED TONGUE & GROOVE INSTALLATION OPTIONS:**
(A) Floating, glue T&G method, over cushioning type underlayment (purchased separately); **(B)** Troweled full-spread glue down to subfloor; **(C)** Staple/Nail direct to wood subfloor

INSTALLATION LOCATIONS: Indoor climate controlled areas (60-80F, 35-55% RH); On / Above / Below Grade; in most rooms (excluding full baths); Over in-floor radiant heat ? (Harris Wood approves Engineered Oak, American Cherry, Walnut Species ONLY); Not approved for use on stairs / treads.

APPROVED SUBFLOORS: Structurally sound, flat, firm, dry, and clean hard surfaces such as plywood, OSB, and concrete (see installation instructions for additional details). When FLOATING only, also particleboard and lightweight concrete.

P65 WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood-dust

PLANK SPECS: 7-1/2" W x 1/2" T x Fixed RL (24" to 95-1/2")			SQ FT / LBS PER CTN (28 PER PLT.)	COORDINATING REAL WOOD MOLDINGS					
WOOD SPECIES (Top Layer)	COLOR	ITEM #		Flush Mount	Reducer	Flush Mount Stairnose	T Mold	Qtr. Rd.	Threshold
WIREBRUSHED TEXTURED SURFACE				All moldings 78" Length. Packed 5 pcs. per ctn.					
RED OAK (<i>Quercus rubra</i>); Janka 1290									
Red Oak (2.0mm)	LeConte	HE96000	29.75/ 45.0	LM7475		LM7476	LM7477	LM7478	LM7479
Red Oak (2.0mm)	Denali	HE96002	29.75/ 45.0	LM7485		LM7486	LM7487	LM7488	LM7489
Hickory (2.0mm)	Bryce	HE96007	29.75/ 45.0	LM7535		LM7536	LM7537	LM7538	LM7539
SMOOTH SURFACE									
WHITE OAK (<i>Quercus alba</i>); Janka 1360									
White Oak (2.0mm)	Wonderland	HE96012	29.75/ 45.0	LM7585		LM7586	LM7587	LM7588	LM7589
HICKORY (<i>Carya spp.</i>); Janka 1820									
Hickory (2.0mm)	Wrangell	HE96015	29.75/ 45.0	LM7610		LM7611	LM7612	LM7613	LM7614
Hickory (2.0mm)	Windom	HE96018	29.75/ 45.0	LM7094		LM7095	LM6257	LM6241	LM6253
Hickory (2.0mm)	Palisade	HE96022	29.75/ 45.0	LM7723		LM7724	LM7725	LM7727	LM7726
RED MAPLE (<i>Acer rubrum</i>); Janka 950									
Red Maple (2.3mm)	Half Dome	HE96019	29.75/ 45.0	LM7700		LM7701	LM7702	LM7704	LM7703
Red Maple (2.3mm)	Olympic	HE96023	29.75/ 45.0	LM7728		LM7729	LM7730	LM7732	LM7731
Red Maple (2.3mm)	Bighorn	HE96021	29.75/ 45.0	LM3995		LM4030	LM3249	LM3263	LM5938

Vintage and Rustic products may contain naturally occurring light and dark wood color and grain variations.

Janka ratings refer to top layer material of product and are for comparison between above collection products.

FEATURES / BENEFITS: Wide & Long Plank Smooth or Wirebrushed Surface real hardwood flooring with a broad selection of colors • Sliced surface veneers create the look of traditional solid hardwood in these engineered plank floors • Traditional Tongue and Groove installation allows multiple methods including floating (glue T&G method over cushioning underlayment), troweled full-spread glue down directly to the subfloor, staple /nail down. • Durable 5-ply real hardwood construction offers maximum stability • Urethane Aluminum Oxide Finish provides superior wear, scuff, gloss reduction, and staining resistance • Hypo-allergenic, does not harbor allergens.

<p>Made In USA Established 1898</p>		<p>MANUFACTURED USING CARB PHASE II AND TSCA TITLE VI COMPLIANT MATERIALS</p>
<p>Harris Wood • 2225 Eddie Williams Road • Johnson City, TN • www.harriswoodfloors.com</p>		